



### Main

|                           |                                                                                                                                                                                                                                                                      |
|---------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Range                     | Square D                                                                                                                                                                                                                                                             |
| Product name              | Classic                                                                                                                                                                                                                                                              |
| Product or component type | Load Center                                                                                                                                                                                                                                                          |
| Device application        | Distribution                                                                                                                                                                                                                                                         |
| Provided equipment        | earth terminal block<br>neutral terminal block<br>blanking plate<br>plug-on mounting rail<br>removable gland plate with cable knockouts at top and bottom of the enclosure<br>removable front cover<br>enclosure<br>125...250 A Easypact circuit breaker at incoming |

### Complementary

|                                    |                                                                                                                                                                                                                                                                                                                                                                                                                                         |
|------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Load center type                   | Main breaker                                                                                                                                                                                                                                                                                                                                                                                                                            |
| Enclosure mounting                 | Surface                                                                                                                                                                                                                                                                                                                                                                                                                                 |
| Number of ways                     | 30 ways (outgoer)                                                                                                                                                                                                                                                                                                                                                                                                                       |
| Electrical connection              | Tin plated copper busbar connection                                                                                                                                                                                                                                                                                                                                                                                                     |
| [In] rated current                 | 250 A                                                                                                                                                                                                                                                                                                                                                                                                                                   |
| Network number of phases           | 3 phases                                                                                                                                                                                                                                                                                                                                                                                                                                |
| Wiring configuration               | 4-wire                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| Short-circuit current              | 25 kA                                                                                                                                                                                                                                                                                                                                                                                                                                   |
| Options for protection device type | QO type miniature circuit breaker (MCB) - 1P in outgoer<br>QO type miniature circuit breaker (MCB) - 3P in outgoer<br>QO type residual current circuit breaker with overcurrent protection (RCBO) - 1P - 10 mA in outgoer<br>QO type residual current circuit breaker with overcurrent protection (RCBO) - 1P - 30 mA in outgoer<br>QO type residual current circuit breaker with overcurrent protection (RCBO) - 2P - 30 mA in outgoer |
| [Ue] rated operational voltage     | 240/415 V AC                                                                                                                                                                                                                                                                                                                                                                                                                            |
| Type of front cover                | Plain blue grey color with cut-out                                                                                                                                                                                                                                                                                                                                                                                                      |
| Door type                          | Plain                                                                                                                                                                                                                                                                                                                                                                                                                                   |
| Door opening side                  | Right or left                                                                                                                                                                                                                                                                                                                                                                                                                           |
| Lock type                          | Keylock (to be ordered separately)<br>Sliding knob                                                                                                                                                                                                                                                                                                                                                                                      |
| Cable entry                        | 3 knock-out at top and bottom                                                                                                                                                                                                                                                                                                                                                                                                           |

|                    |                                                       |
|--------------------|-------------------------------------------------------|
|                    | 2 knock-out at left side<br>2 knock-out at right side |
| Enclosure material | Phosphated cold rolled steel of 1.4 mm thickness      |
| Type of paint      | Polyester epoxy powder 50...60 µm                     |
| Colour             | Blue grey                                             |
| Height             | 755 mm external:                                      |
| Width              | 381 mm external:                                      |
| Depth              | 130 mm external:                                      |

## Environment

|                         |                                          |
|-------------------------|------------------------------------------|
| Standards               | TIS 1436-2540<br>BS 5486-13<br>IEC 60439 |
| IP degree of protection | IP4X                                     |
| Product certifications  | TIS                                      |

## Offer Sustainability

|                   |                                                                                                   |
|-------------------|---------------------------------------------------------------------------------------------------|
| EU RoHS Directive | Pro-active compliance (Product out of EU RoHS legal scope)<br><a href="#">EU RoHS Declaration</a> |
|-------------------|---------------------------------------------------------------------------------------------------|