

Cooling Solutions



Cabinet Air Conditioner

Application: Industrial field cabinet climate control.

- 220VAC and 48VDC power options
- Intelligent controller, RS485 communication (MODBUS protocol), alarm output, 4~20mA temp/humidity signal output.
- Built in high efficiency brand EBM blowers; Highly Compressor and Phoenix terminals.
- Cooling Capacity: 300W; 500W; 800W; 1000W; 2000W; 3000W; 4000W (Can be customized.)



Air-air Heat Exchanger

Application: Industrial control cabinet; Smart grid outdoor cabinet; Tele-communication cabinet; Battery cabinet etc.

- 220VAC and 48VDC power options
- Intelligent controller, RS485 communication (MODBUS protocol), alarm output, 4~20mA temp/humidity signal output, up to support 128 units network operation.
- Cooling Capacity: 50W; 60W; 80W; 100W; 120W; 150W; 180W (Can be customized.)

Thermoelectric Air Conditioner



Peltier Liquid to Air Cooler

SDLA-60-12



Peltier Air to Air Cooler

SD-070-12



Peltier Air to Air Cooler

SD-100-24



TEC Air Conditioner

SDC2-300-48

- Extremely reliable solid state construction (Alluminum Alloy) with long life span
- Maintenance-free with no moving parts
- No compressor, refrigerant or filters
- Compact size, lightweight, convenient to install and operate
- 12VDC 24VDC 48VDC power options
- 20W~300W cooling capacity options (Can be customized.)

Semiconductor Dehumidifier



Aluminium Alloy

SDCS-E60S



Sheet Metal

SDCS-E60C



Big Capacity 120W

SDCS-E120L



Stainless Steel

SDCS-E60B

Email: sanda04@digitalmeter-suppliers.com
Mobile/Skype/Whatsapp: +86 135 0733 2869
<http://sandaenvicool.com/>
<http://www.digitalmeter-suppliers.com/>
ADD: No. 502, Wuli Dun Industry Zone, Liling, Zhuzhou, Hunan, China Zip code: 412205

Tel: +86 731 8853 9799
Fax: +86 731 8620 6577

Microprocessor intelligent protection relay



SDW5001



SDW8001


Combined Overcurrent & Earth Fault Relay



SD2200



SD1000A



Temperature Controller



PID Temp Controller
SD-TBS



LED Digital Temp Controller
SD-ZW9200



Thermostat
ZR 001/MFR 012

Digital Meters



Multi-function network meter
SD994Z-9S4



Multi-function electric meter
SD994E-9S4



Single phase voltmeter
SD994AV-9K1



Three phase active power meter
SD994P3-9K1



Three phase ammeter
SD994AI-9K4



Three phase voltmeter
SD994AV-9K4

Switchgear Simulator Control Panel



SD-CK9500B

LED Display



SD-CK9600

LCD Display



SD-KG6000

Status Indicator



SD-CW2100

Wireless Temperature
Measurement



Cross Flow Cooling Fan



GFDD470-150 Top-blow



GFDD590-150 Side-blow

Dry-type Transformer Temp Controller



BWD-4K130 (Plastic)



BWD-3K130 (Plastic)



BWDC-2706 (Metal)



SD3K330C(RS485)

- 3 Channels Transformer Temperature Monitor
- Dry contact relay output, ALARM, TRIP, FAULT signal operation and start ventilation system (FAN)
- Password design allows certain users to have full configuration access and others, set points only
- Non-volatile memory storage of per-channel temperatures for recall in the event of power-loss
- Large 5-digit LED display allows easy programming
- RS485 and 4~20mA for options