



CROWN EXTRA LIGHTING CO., LTD



SPECIFICATION FOR APPROVAL

CUSTOMER _____
MODEL NO. **GYD680 SERIES**
PART NO. _____
APPLICATION _____
ISSUE DATE _____
REV. NO. _____
REV.DATE **2020.10.23**

FOR CUSTOMER APPROVAL	CHECKED BY
	Ivy
	APPROVED BY





■ **Features:**

- Zone 1&2, Zone 21&22
- Instant on crisp white light output
- High efficiency drivers and LEDs provide, low cost operation in harsh and heavy industrial applications
- Isolated LED compartment reduces temperature within driver housing
- Multi choice of beam angle for 60° 90° 120°

Applications

- Typical applications include:
- Oil and gas industries
- Chemical, petrochemical
- Pharmaceutical industries
- Pulp and Paper
- Waste and sewage treatment
- Power Generation

Standard Materials

- Housing: Die-casting aluminum
- Exterior: Stainless steel
- Globe: Tempered glass
- Gasket: Silicon rubber

Certifications

- ATEX
- CNEX
- CE
- RoHS
- ISO9001

GYD680-1



GYD680-2



Explosion protection

Ex Mark	Ex d IIC T6 Gb Ex tD A21 IP66 T80°C
For use in	Zone 1, 2 & Zone 21, 22

Electrical data

Rated voltage	100-305 VAC, 50-60Hz
Power factor	>0.98
THD	<20%

Luminous characteristics

Power consumption [W]	50-100	100-200
Colour rendering [CRI]	70 (±2)	
Colour temperature [K]	3000-6500	
Luminaire efficiency [Lm/W]	130-145	
Beam angle	120° (60°, 90° optical len is optional)	



Mechanical data

Degree of protection	IP66	
Cable entry	G 3/4"; NPT3/4"	
Weight [kg]	7.25	8.6
Terminal	≤2.5 mm ²	
Mounting Styles	Ceiling; Wall Bracket; Pendant	



50-200W LED explosion proof light

GYD680series

Dimension [mm]




GYD6801




GYD6802

Installation




Ceiling Mount




Pendant

50-200W LED explosion proof light


GYD680series




Wall Mount



Wall Mount II



Stanchion I



Stanchion II