

# CROWN EXTRA LIGHTING CO., LTD

Distributor: www.7-mars.com



# **SPECIFICATION FOR APPROVAL**

CUSTOMER	
MODEL NO.	GYD970 SERIES
PART NO.	
APPLICATION	
ISSUE DATE	
REV. NO.	
REV.DATE	2022.03.28

FOR CUSTOMER APPROVAL	CHECKED BY
	Jason
	APPROVED BY









#### **■** Features:

- Zone 1&2, Zone 21&22
- Instant on crisp white light output
- High efficiency drivers and LEDs provide, low cost operation in harsh and heavy industrial applications
- Isolated LED compartment reduces temperature within driver housing
- Multi choice of beam angle for 45° 90° 120°

## **Applications**

- Typical applications include:
- Oil and gas industries
- Chemical, petrochemical
- Pharmaceutical industries
- Pulp and Paper
- Waste and sewage treatment
- Power Generation

## **Standard Materials**

Housing: Die-casting aluminum
 Exterior: Stainless steel
 Globe: Tempered glass
 Gasket: Silicon rubber

#### **Certifications**

ATEX CNEX CE RoHS ISO9001



GYD970-1

GYD970-2

GYD970-3

GYD970-4









# **Explosion protection**

European (ATEX) Gas and Dust	<b>C€1282</b>
	<b>C€1282</b>
For use in	Zone 1, 2 & Zone 21, 22

### **Electrical data**

Rated voltage	100-277VAC, 50-60Hz
Power factor	>0.95
THD	<20%


## **Luminous characteristics**


Power consumption [W]	20 ~ 80	100~120	150~200	200-240
Colour rendering [CRI]	80 (±2)			
Colour temperature [K]	5700			
Luminaire efficiency	115-145			
[Lm/W]	110-140			
Beam angle	120° (45°, 90° is o	ptional)		

### Mechanical data


Degree of protection	IP66			
Cable entry	G 3/4"; NPT 3/4"			
Weight [kg]	5.12	9	12	16
Terminal	≤2.5 mm²			
Mounting Styles	Ceiling; Wall Bracket; Pendant			

# Dimension [mm]







	Α	В	С	D	Е	F	G	Н
GYD970-1	304	264	219	180	126	216	227	219
GYD970-2	384	344	273	240	126	255	277	273
GYD970-3	472	418	315	275	130	295	320	315
GYD970-4	544	492	371	330	130	341	374	371




## Installation



**Ceiling Mount** 



**Bracket Mount** 



Wall Mount