

Product data sheet

Specifications



M1/M1E processor adaptor - 1 Modbus - 20 MHz

171CCS70000

⚠ Discontinued on: 31 May 2015

⚠ To be end-of-service on: 31 May 2023

⚠ Discontinued - Service only

Main

Range of product	Modicon Momentum automation platform
Product or component type	M1/M1E processor adaptor
Software designation	Concept version V2.6 Modsoft version >= V2.5 ProWORX NxT version V2.0 ProWORX 32
Communication port protocol	Modbus
Processor name	X 86 based (INTEL, AMD)
Clock frequency	20 MHz

Complementary

Discrete I/O processor capacity	2048 I/2048 O
Memory type	256 kB flash 64 kB RAM
Memory description	Program memory 2.4 kB LL984 Data 2 kB
Material	Lexan
Word length	16 bit
[Us] rated supply voltage	5.0 V DC +/-5 %
Supply	By Momentum I/O base
Exact time for 1 Kinstruction	1 ms
Register I/O processor capacity	2048 I/2048 O
Number of port	1 RS232C non isolated
Marking	CE
Net weight	0.042 kg

Environment

Protective treatment	TC
Ambient air temperature for operation	0...60 °C
Ambient air temperature for storage	-40...85 °C

Relative humidity	5...96 % without condensation
Operating altitude	2000 m
Shock resistance	<= 15 gn peak 11 ms half sine wave acceleration
Vibration resistance	0.75 mm d.a 1 gn
Product certifications	UL cUL FM Class 1 Division 2 Nema type 250

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	5.5 cm
Package 1 Width	18.0 cm
Package 1 Length	26.0 cm
Package 1 Weight	206.0 g
Unit Type of Package 2	S03
Number of Units in Package 2	8
Package 2 Height	30.0 cm
Package 2 Width	30.0 cm
Package 2 Length	40.0 cm
Package 2 Weight	2.163 kg

Contractual warranty

Warranty	18 months
----------	-----------

Recommended replacement(s)

171CCS70000 is replaced by:

1x



Unity M1E processor - RS232/485 - Ethernet - USB - I/O bus
171CBU98090