

Product data sheet

Specifications



Unity processor Modicon Quantum - 1056 kB - 66 MHz

140CPU43412U

- ❗ Discontinued on: 31 December 2018
- ❗ To be end-of-service on: 31 December 2026

❗ Discontinued - Service only

Main

Range of product	Modicon Quantum automation platform
Product or component type	Unity processor

Complementary

Clock frequency	66 MHz
Number of slots	2 4 10 16 6
Number of racks	2 - local rack(s)
Number of distributed I/O station	63 station(s) - 1 rack(s) - 3 Modbus Plus network(s)
Number of remote I/O station	31 - 2 rack(s) per S908 remote I/O 0 - 0 rack(s) per ethernet remote I/O
Discrete I/O number	31744 inputs, 31744 outputs - remote 8000 inputs, 8000 outputs - distributed - per network Modbus Plus Unlimited (26 slots max) - local
Analogue I/O number	500 inputs, 500 outputs - distributed - per network Modbus Plus 1984 inputs,1984 outputs - S908 remote I/O Unlimited (26 slots max) - local
Application specific I/O	Serial link Counter High-speed interrupt inputs Accurate time stamping
Number of optional modules	6 (Ethernet, Modbus, Modbus Plus, Profibus DP, Sy/Max)
Maximum number of connections	2 AS-Interface - distributed 2 Modbus (RS232/485 Modbus/ASCII) 4 AS-Interface - remote 6 Ethernet TCP/IP - local 6 Modbus Plus - local 6 Profibus DP - local
Integrated connection type	1 Modbus Plus with 2 Modbus with
Checks	Process control
Memory description	Internal RAM 1056 kB
Switch function	Key switch memory start/stop memory protection Slide switch communication port : ASCII/RTU/Memory
Application structure	1 cyclic/periodic master task - 1 periodic fast task -

	16 timer interrupt tasks - 64 I/O interrupt tasks - 64 interrupt tasks - No auxiliary task -
Execution time per instruction	0.1...0.27 µs floating points 0.1...0.27 µs on fixed-point arithmetic 0.12...0.585 µs Boolean 0.12...0.585 µs on word
Number of instructions per ms	1.86 Kinst/ms 100 % Boolean 2.49 Kinst/ms 65 % Boolean and 35 % numerical
System overhead	0.2 ms for fast task 1 ms for master task
Bus current requirement	1800 mA
Local signalling	1 LED (green) for communications are active on the Modbus Plus port (Modbus Plus) 1 LED (green) for communications are active on the Modbus port (Modbus) 1 LED (green) for CPU has been started and is solving logic (RUN) 1 LED (green) for CPU has passed the power-up diagnostic tests (READY) 1 LED (orange) for write-protected memory (memory port) 1 LED (red) for battery needs replacing or is not present (BAT LOW) 1 LED (red) for communications error on the Modbus Plus port (ERROR A)
Electrical connection	1 female connector, connector type: SUB-D 9 for connecting to the Modbus Plus network 2 female connectors, connector type: SUB-D 9 for connecting to the Modbus bus

Environment

Product certifications	CSA CE UL
Standards	HazLoc

Packing Units


Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	4.5 cm
Package 1 Width	15.5 cm
Package 1 Length	31.0 cm
Package 1 Weight	607.0 g
Unit Type of Package 2	S03
Number of Units in Package 2	7
Package 2 Height	30.0 cm
Package 2 Width	30.0 cm
Package 2 Length	40.0 cm
Package 2 Weight	4.249 kg

Contractual warranty

Warranty	18 months
----------	-----------

Racks for Modules Mounting

Dimensions of Modules and Racks



Recommended replacement(s)

140CPU43412U is replaced by:

1x



Standalone processor, Modicon M580, 4MB, 61 Ethernet devices, 4 Local I/O racks
(1024 Digital, 256 Analog)
BMEP581020