

# Product data sheet

Specifications



## RIO drop adaptor module Modicon Quantum - 1 connector with single cable

140CRA93100C

! Discontinued on: 31 December 2021

! To be end-of-service on: 31 December 2029

! Discontinued - Service only

### Main

Range of product	Modicon Quantum automation platform
Product or component type	RIO drop adaptor module

### Complementary

Product compatibility	Quantum
Maximum number of I/O expansion module	27
Type of cable	75 Ohm coaxial cable
Transmission rate	1544 Mbit/s
Dynamic range	35 dB
Isolation voltage	500 V DC coaxial center and ground
Electrical connection	1 female connector F, elbowed with single cable
Diagnostics startup	Power up and runtime RAM address/data Executive checksum
Power dissipation in W	3 W 1 channel
Bus current requirement	600 mA 1 channel
Module format	Standard

### Environment

Protective treatment	Conformal coating Humiseal 1A33
Standards	CSA C22.2 No 142 CUL UL 508
Resistance to electrostatic discharge	4 kV contact conforming to IEC 801-2 8 kV on air conforming to IEC 801-2
Resistance to electromagnetic fields	10 V/m 80...1000 MHz conforming to IEC 801-3
Ambient air temperature for operation	0...60 °C
Ambient air temperature for storage	-40...85 °C
Relative humidity	95 % without condensation

---

Operating altitude	<= 5000 m
--------------------	-----------

## Packing Units

---

Unit Type of Package 1	PCE
------------------------	-----

---

Number of Units in Package 1	1
------------------------------	---

---

Package 1 Height	5.0 cm
------------------	--------

---

Package 1 Width	17.0 cm
-----------------	---------

---

Package 1 Length	31.0 cm
------------------	---------

---

Package 1 Weight	522.0 g
------------------	---------

---

Unit Type of Package 2	S03
------------------------	-----

---

Number of Units in Package 2	7
------------------------------	---

---

Package 2 Height	30.0 cm
------------------	---------

---

Package 2 Width	30.0 cm
-----------------	---------

---

Package 2 Length	40.0 cm
------------------	---------

---

Package 2 Weight	4.169 kg
------------------	----------

## Offer Sustainability

---

Sustainable offer status	Green Premium product
--------------------------	-----------------------

---

REACH free of SVHC	Yes
--------------------	-----

---

EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) <a href="#">EU RoHS Declaration</a>
-------------------	---

---

Mercury free	Yes
--------------	-----

---

RoHS exemption information	<a href="#">Yes</a>
----------------------------	---------------------

---

China RoHS Regulation	<a href="#">China RoHS declaration</a>
-----------------------	--

---

Environmental Disclosure	<a href="#">Product Environmental Profile</a>
--------------------------	---

---

Circularity Profile	<a href="#">End of Life Information</a>
---------------------	---

---

WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
------	---

---

California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a>
---------------------------	---


## Contractual warranty

---

Warranty	18 months
----------	-----------

**Racks for Modules Mounting**

**Dimensions of Modules and Racks**



- (1) 2 slots
- (2) 3 slots
- (3) 4 slots
- (4) 6 slots
- (5) 10 slots
- (6) 16 slots

**Recommended replacement(s)**

140CRA93100C is replaced by:

1x



EIO drop adapter, Modicon X80, with Ethernet backplane, coated  
BMECRA31210C