Product datasheet





motion servo drive, Lexium 32, 72A, three phase, supply voltage 208 to 480V, 7kW, modbus

LXM32CD72N4

Main

IVIAIII			
Range of product	Lexium 32		
Device short name	LXM32C		
Product or component type	Motion servo drive		
Format of the drive	Book		
Network number of phases	Three phase		
[Us] rated supply voltage	200240 V - 1510 % 380480 V - 1510 %		
Supply voltage limits	170264 V 323528 V		
Supply frequency	50/60 Hz - 55 %		
Network frequency	47.563 Hz		
EMC filter	Integrated		
Continuous output current	24 A at 8 kHz		
Output current 3s peak	72 A at 208 V for 5 s 72 A at 480 V for 5 s		
maximum continuous power	6500 W at 208 V 13000 W at 400 V 13000 W at 480 V		
Nominal power	5 kW at 208 V 8 kHz 7 kW at 400 V 8 kHz 7 kW at 480 V 8 kHz		
Line current	21.1 A 34 % at 208 V, with external line choke of 1 mH 22.5 A 45 % at 400 V, with external line choke of 1 mH 19.5 A 55 % at 480 V, with external line choke of 1 mH 21.9 A 106 % at 208 V, without line choke 17.3 A 126 % at 400 V, without line choke 14.6 A 129 % at 480 V, without line choke		

Complementary

switching frequency	8 kHz	
Overvoltage category	III	
Maximum leakage current	30 mA	
Output voltage	<= power supply voltage	
Electrical isolation	Between power and control	
Type of cable	Single-strand IEC cable (temperature: 50 °C) copper 90 °C XLPE/EPR	
Electrical connection	Terminal, clamping capacity: 3 mm², AWG 12 (CN8) Terminal, clamping capacity: 5 mm², AWG 10 (CN1) Terminal, clamping capacity: 5 mm², AWG 10 (CN10)	

CN8: 0.5 N.m CN1: 0.7 N.m CN10: 0.7 N.m			
Discrete input number	2 safety discrete input(s) 6 logic discrete input(s)		
Discrete input type	Logic (DI terminals) Safety (compliment of STO_A, compliment of STO_B terminals)		
Sampling duration	ANA1+/ANA1-, ANA2+/ANA2-: 0.25 ms analog DI: 0.25 ms discrete		
Discrete input voltage	24 V DC for logic 24 V DC for safety		
Discrete input logic	Positive (compliment of STO_A, compliment of STO_B) at State 0: < 5 V at State 1: > 15 V conforming to EN/IEC 61131-2 type 1 Positive (DI) at State 0: > 19 V at State 1: < 9 V conforming to EN/IEC 61131-2 type 1		
	Positive or negative (DI) at State 0: < 5 V at State 1: > 15 V conforming to EN/IEC 61131-2 type 1		
Response time	<= 5 ms compliment of STO_A, compliment of STO_B		
Discrete output number	5		
Discrete output type	Logic output(s) (DO)24 V DC		
Discrete output voltage	<= 30 V DC		
Discrete output logic	Positive or negative (DO) conforming to EN/IEC 61131-2		
Contact bounce time	<= 1 ms for compliment of STO_A, compliment of STO_B 0.25 μs1.5 ms for DI		
Braking current	50 mA		
Analogue input number	2		
Response time on output	250 μs (DO) for discrete output(s)		
Absolute accuracy error	< +/- 0.5 %		
Linearity error	< +/- 0.1 %		
Analogue input type	ANA1+/ANA1-, ANA2+/ANA2- analog input: differential +/- 10 V, impedance: >= 20 Ohm, resolution: 14 bits		
Control signal type	Servo motor encoder feedback Pulse train output (PTO) RS422 <500 kHz <100 m Pulse/direction (P/D), A/B, CW/CCW 5 V, 24 V link (open collector) <10 kHz <1 m Pulse/direction (P/D), A/B, CW/CCW 5 V, 24 V link (push-pull) <200 kHz <10 m Pulse/direction (P/D), A/B, CW/CCW RS422 <1000 kHz <100 m		
Protection type	Against reverse polarity: inputs signal Against short-circuits: outputs signal		
Safety function	STO (safe torque off), integrated		
Safety level	SIL 3 conforming to EN/IEC 61508 PL = e conforming to ISO 13849-1		
Communication interface	Modbus, integrated		
Connector type	RJ45 (labelled CN7) for Modbus		
commissioning port	2-wire RS485 multidrop for Modbus		
Transmission rate	9600, 19200, 38400 bps for bus length of 40 m for Modbus		
Number of addresses	1247 for Modbus		
Status LED	1 LED (red) servo drive voltage		
Signalling function	Display of faults 7 segments		
Marking	CE		
Operating position	Vertical +/- 10 degree		

Product compatibility	Servo motor BMH (140 mm, 2 motor stacks)		
	Servo motor BMH (140 mm, 3 motor stacks)		
	Servo motor BMH (190 mm, 1 motor stacks)		
	Servo motor BMH (190 mm, 2 motor stacks)		
	Servo motor BMH (190 mm, 3 motor stacks)		
	Servo motor BMH (205 mm, 3 motor stacks)		
	Servo motor BSH (140 mm, 2 motor stacks)		
	Servo motor BSH (140 mm, 3 motor stacks)		
	Servo motor BSH (140 mm, 4 motor stacks)		
Width	108 mm		
Height	270 mm		
Depth	237 mm		
Net weight	4.8 kg		

Environment

Electromagnetic compatibility	Conducted EMC, class A group 1 conforming to EN 55011 Conducted EMC, class A group 2 conforming to EN 55011 Conducted EMC, environment 2 category C3 conforming to EN/IEC 61800-3 Conducted EMC, category C2 conforming to EN/IEC 61800-3 Conducted EMC, environments 1 and 2 conforming to EN/IEC 61800-3 Electrostatic discharge immunity test, level 3 conforming to EN/IEC 61000-4-2 Susceptibility to electromagnetic fields, level 3 conforming to EN/IEC 61000-4-3 1.2/50 µs shock waves immunity test, level 3 conforming to EN/IEC 61000-4-5 Electrical fast transient/burst immunity test, level 4 conforming to EN/IEC 61000-4-4 Radiated EMC, class A group 2 conforming to EN 55011 Radiated EMC, category C3 conforming to EN/IEC 61800-3	
Standards	EN/IEC 61800-5-1 EN/IEC 61800-3	
Product certifications	UL TÜV CSA	
IP degree of protection	IP20 conforming to EN/IEC 60529 IP20 conforming to EN/IEC 61800-5-1	
Vibration resistance	1 gn (f= 13150 Hz) conforming to EN/IEC 60068-2-6 1.5 mm peak to peak (f= 313 Hz) conforming to EN/IEC 60068-2-6	
Shock resistance	15 gn for 11 ms conforming to EN/IEC 60028-2-27	
Pollution degree	2 conforming to EN/IEC 61800-5-1	
Environmental characteristic	Classes 3C1 conforming to IEC 60721-3-3	
Relative humidity	Class 3K3 (5 to 85 %) without condensation conforming to IEC 60721-3-3	
Ambient air temperature for operation	050 °C conforming to UL	
Ambient air temperature for storage	-2570 °C	
Type of cooling	Integrated fan	
Operating altitude	<= 1000 m without derating > 10003000 m with conditions	

Packing Units

•	
Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	14.5 cm
Package 1 Width	27.5 cm
Package 1 Length	33 cm
Package 1 Weight	5.507 kg
Unit Type of Package 2	S03

Number of Units in Package 2	2
Package 2 Height	30 cm
Package 2 Width	30 cm
Package 2 Length	40 cm
Package 2 Weight	11.809 kg
Unit Type of Package 3	P06
Number of Units in Package 3	16
Package 3 Height	75.0 cm
Package 3 Width	40.0 cm
Package 3 Length	80.0 cm
Package 3 Weight	113.112 kg

Contractual warranty

Warranty 18 months



Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO2 products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

Well-being performance

	Mercury Free	
⊘	Rohs Exemption Information	Yes
⊘	Pvc Free	


Certifications & Standards

Circularity Profile	End of Life Information	
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins	
Environmental Disclosure	Product Environmental Profile	
China Rohs Regulation	China RoHS declaration	
Eu Rohs Directive	Pro-active compliance (Product out of EU RoHS legal scope)	
Reach Regulation	REACh Declaration	

Dimensions Drawings

Lexium 32 Servo Drive


Dimensions



Mounting and Clearance

Lexium 32 Motion Control Servo Drives

Mounting Recommendations



LXM32•U45M2, •U90M2 and LXM32•U60N4 servo drives are cooled by natural convection. LXM32•D18M2, •D30M2, LXM32 •D12N4, •D18N4, •D30N4 and •D72N4servo drives have an integrated fan.

When installing the servo drive in the enclosure, follow the instructions below with regard to the temperature and protection index:

- Provide sufficient cooling of the servo drive
- Do not mount the servo drive near heat sources
- . Do not mount the servo drive on flammable materials
- Do not heat the servo drive cooling air by currents of hot air from other equipment and components, for example from an external braking resistor
- Mount the servo drive vertically (± 10%)
- If the servo drive is used above its thermal limits, control stops due to overtemperature

NOTE: For cables that are connected via the underside of the servo drive, a free space ≥ 200 mm/7.87 in. is required under the unit to comply with the bending radius of the connection cables.

Ambient temperature	Mounting distances	Instructions to be followed
0°C+ 50°C	d ≥ 0 mm	-
+ 50°C+ 60°C	d ≥ 0 mm	Reduce the output current by 2.2% per °C above 50°C

NOTE: Do not use insulated enclosures, as they have a poor level of conductivity.


Recommendations for Mounting in an Enclosure

To ensure good air circulation in the servo drive:

- Fit ventilation grilles on the enclosure.
- Ensure that ventilation is adequate, otherwise install a forced ventilation unit with a filter.

Product datasheet

LXM32CD72N4



- (1) Natural convection
- (2) Forced ventilation
 - Any apertures and/or fans must provide a flow rate at least equal to that of the servo drive fans (refer to characteristics).
 - Use special filters with IP 54 protection.

Mounting in Metal Enclosure (IP 54 Degree of Protection)

The servo drive must be mounted in a dust and damp proof enclosure in certain environmental conditions, such as dust, corrosive gases, high humidity with risk of condensation and dripping water, splashing liquid, etc. In these cases, Lexium 32 servo drives can be installed in an enclosure where the internal temperature must not exceed 60°C.