# **Product datasheet**

Specifications





Safety switch, general duty, fusible, 60A, 2 pole, 15hp, 240VAC, NEMA 3R, bolt on provision, neutral factory installed

D222NRB

### Main

Single Throw Safety Switch	
General duty	
Residential	
Fusible disconnect switch	
Neutral (factory installed)	
1 phase	
2	
60 A	
240 V AC	
NEMA 3R	
1.5 hp at 120 V AC 60 Hz for 1 phase motors 3 hp at 120 V AC 60 Hz for 3 phases motors 3 hp at 240 V AC 60 Hz for 1 phase motors 7.5 hp at 240 V AC 60 Hz for 3 phases motors 10 hp at 240 V AC 60 Hz for 1 phase motors 15 hp at 240 V AC 60 Hz for 3 phases motors	

## Complementary

Short Circuit Current Rating	100 kA maximum depending on fuse H, K or R	
Fuse type	H, K or R	
Mounting Type	Surface	
Electrical Connection	Lugs	
Wiring configuration	3-wire	
Wire Size	AWG 12AWG 3 aluminium AWG 14AWG 3 copper	
Tightening torque	4.0 N.m for 2.085.26 mm² (AWG 14AWG 10) 4.0 N.m (AWG 14AWG 10) 5.08 N.m for 8.37 mm² (AWG 8) 5.08 N.m for 12.321.12 mm² (AWG 6AWG 4) 5.6 N.m for 26.67 mm² (AWG 3)	
Depth	123.70 mm	
Width	189.23 mm	
Height	377.95 mm	
Net weight	4 kg	

### **Environment**

Certifications UL listed file E2875

## **Packing Units**

•	
Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	13.03 cm
Package 1 Width	19.38 cm
Package 1 Length	40.97 cm
Package 1 Weight	3.79 kg
Unit Type of Package 2	PAL
Number of Units in Package 2	120
Package 2 Height	114.3 cm
Package 2 Width	101.6 cm
Package 2 Length	121.92 cm
Package 2 Weight	463.571 kg

## **Contractual warranty**

Warranty 18 months



Green Premium<sup>TM</sup> label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO2 products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

### Well-being performance

	Mercury Free	
<b>⊘</b>	Rohs Exemption Information	Yes
<b>⊘</b>	Pvc Free	

### **Certifications & Standards**

Reach Regulation	REACh Declaration
Eu Rohs Directive	Compliant with Exemptions
China Rohs Regulation	China RoHS declaration  Product out of China RoHS scope. Substance declaration for your information
Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations