



www.suntexcomposite.com

TECHNICAL DATA SHEET

STYLE: TGF1250-GP235-5003

DESCRIPTION

TGF1250-GP235-5003 is a heavy weight woven texturized fiberglass fabric coated with a specially formulated graphite and polyurethane solution which provides high temperature and abrasion resistance properties for the manufacturer of gaskets, flexible expansion joints, removable jackets and other types of fire control systems.

BASE FABRIC

Base fabric style No. TGF1250

	<u>(Metric)</u>	<u>(English)</u>	<u>Test methods</u>
Weave	Plain	Plain	
Yarn			
Warp	ET9 1250 tex	ETG 4.0	
Weft	ET9 2500 tex	ETG 2.0	
Construction			
Warp	5 ± 0.6 ends/cm	13 ± 2 ends/inch	ASTM D 3775-96
Weft	2.5 ± 0.5 picks/cm	6 ± 1 picks/inch	ASTM D 3775-96
Weight	1250 ± 50 g/m ²	36.7 ± 1.5 oz/yd ²	ASTM D3776-96
Thickness	1.4 ± 0.1 mm	0.055 ± 0.005 inch	ASTM D1777-96

COATED FABRIC

Coating style No. GP235-5003

Coating	Graphite coated on both sides		
Weight	1400 ± 50 g/m ²	41.17 ± 1.5 oz/yd ²	ASTM D3776-96
Thickness	1.6 ± 0.05 mm	0.063 ± 0.002 inch	ASTM D1777-96
Color	Black		
Temp resistance	700°C	1300°F	

All data in this specification sheet are representative which we believe to be accurate, but is given without guarantee or responsibility on our part. Anyone intending to use recommendation herein should make their own assessment of the suitability for the purpose required.

SUNTEX COMPOSITE INDUSTRIAL CO., LTD.
1212 Fortune International Building, 717 Wuluo Road, Wuhan
CHINA 430072
Tel: +86-27-878 69 042
Fax: +86-27-871 64 892