



RST Refillable Traps



RST refillable trap


The RST traps are made from 304 stainless steel, and when specified with stainless steel filtration media, are fully suited for corrosive applications. The media is inserted directly into the trap. This ensures direct contact with the trap walls. There is no oil path between the trap wall and the retainer gasket to reduce trap effectiveness.

Advantages to the User

- Refillable
- Two filtration media
- Easy to clean
- Easy to recharge
- KF flanges

Applications

Foreline traps are utilized whenever long-term effects of mechanical pump oil back migration into the pumped chamber or higher vacuum (oil diffusion) pump may be undesirable. Copper wool for standard applications and stainless steel wool for corrosive applications are available.



Dimensional drawing for the RST

Technical Data	RST16KF	RST25KF	RST40KF	
Connection to pump	TRIVAC	D 4/8 B/BCS	D 16/25 B/BCS	D 40/65 B/BCS
Ordering Information	RST16KF	RST25KF	RST40KF	
RST16KF	Part No.			
1.9 lb (0.9 kg)	99 171 135	-	-	
RST25KF		Part No.		
2.6 lb (1.2 kg)		99 171 136	-	
RST40KF			Part No.	
4.1 lb (1.9 kg)			99 171 137	
Filtering media				
Stainless steel	Part No.	Part No.	Part No.	
	99 171 141	99 171 141	99 171 141	
RF copper	Part No.	Part No.	Part No.	
	99 171 145	99 171 146	99 171 147	
BUNA-N gasket	Part No.	Part No.	Part No.	
	725 80 005	725 80 006	725 80 007	