

Product data sheet

Specifications



M1/M1E processor adaptor - 1 Modbus, 1 I/O bus - 32 MHz

171CCC76010

⚠ Discontinued on: 31 May 2015

⚠ To be end-of-service on: 31 May 2023

⚠ Discontinued - Service only

Main

Range of product	Modicon Momentum automation platform
Product or component type	M1/M1E processor adaptor
Software designation	Concept version V2.6 Modsoft version >= V2.5 ProWORX NxT version V2.0 ProWORX 32
Communication port protocol	Modbus
Processor name	X 86 based (INTEL, AMD)
Clock frequency	32 MHz

Complementary

Discrete I/O processor capacity	8192 I/8192 O
Memory type	512 kB flash 512 kB RAM
Memory description	Program memory 18 kB LL984 Program memory 240 kB IEC Data 24 kB
Material	Lexan
Word length	16 bit
[Us] rated supply voltage	5.0 V DC +/-5 %
Supply	By Momentum I/O base
Exact time for 1 Kinstruction	1 ms
Register I/O processor capacity	26048 I/26048 O
I/O limit processor capacity	8192 bits max
I/O words/drop	128 I/O Concept 80 I/O ProWORX
Number of port	1 I/O bus 1 RS232C non isolated
Marking	CE
Net weight	0.042 kg

Environment

Protective treatment	TC
----------------------	----

Ambient air temperature for operation	0...60 °C
Ambient air temperature for storage	-40...85 °C
Relative humidity	5...96 % without condensation
Operating altitude	2000 m
Shock resistance	<= 15 gn peak 11 ms half sine wave acceleration
Vibration resistance	0.75 mm d.a 1 gn
Product certifications	FM Class 1 Division 2 UL Nema type 250 cUL

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	5.5 cm
Package 1 Width	18 cm
Package 1 Length	26 cm
Package 1 Weight	215 g
Unit Type of Package 2	S02
Number of Units in Package 2	4
Package 2 Height	15 cm
Package 2 Width	30 cm
Package 2 Length	40 cm
Package 2 Weight	1.142 kg
Unit Type of Package 3	S03
Number of Units in Package 3	8
Package 3 Height	30 cm
Package 3 Width	30 cm
Package 3 Length	40 cm
Package 3 Weight	2.235 kg

Contractual warranty

Warranty	18 months
----------	-----------

Recommended replacement(s)

171CCC76010 is replaced by:

1x



Unity M1 processor - RS232/485 - USB - I/O bus
171CBU78090