

เอกสารข้อมูลผลิตภัณฑ์

ข้อมูลจำเพาะ



DIO head-end adaptor Modicon Quantum - 2 Modbus+RS485 twisted pair redundant cu

140NOM21200

- ❗ เลิกจำหน่ายในวันที่ 31 ธันวาคม 2565
- ❗ สิ้นสุดในการให้บริการเร็วๆ นี้ในวันที่ 31 ธันวาคม 2573

⚠ กำลังจะยกเลิกการขาย

Main

Range of product	Modicon Quantum automation platform
Product or component type	DIO head-end adaptor

Complementary

Product compatibility	140CRA21210 140CRA21220
Number of port	1 Modbus RS232 twisted pair redundant copper 2 Modbus Plus RS485 twisted pair redundant copper
Transmission rate	1 Mbit/s
I/O words	30 I/32 O
Checks	RAM Processor RAM address Checksum
Power dissipation in W	4 W
Bus current requirement	780 mA

Environment

Resistance to electrostatic discharge	4 kV contact conforming to IEC 801-2 8 kV on air conforming to IEC 801-2
Resistance to electromagnetic fields	10 V/m 80...2000 MHz conforming to IEC 801-3
Ambient air temperature for operation	0...60 °C
Ambient air temperature for storage	-40...85 °C
Relative humidity	95 % without condensation
Operating altitude	<= 5000 m
Standards	UL 508
Product certifications	CSA FM Class 1 Division 2 GOST GL RINA RMRS DNV C-Tick

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	4.6 cm
Package 1 Width	16.0 cm
Package 1 Length	31.0 cm
Package 1 Weight	493.0 g
Unit Type of Package 2	S03
Number of Units in Package 2	7
Package 2 Height	30.0 cm
Package 2 Width	30.0 cm
Package 2 Length	40.0 cm
Package 2 Weight	3.927 kg

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Contractual warranty

Warranty	18 months
----------	-----------

Dimensions of Modules and Racks