



Line-M-20I, Centralizer module with 20 digital inputs

Code: M58E06.

> Protocol: Modbus/RTU > Communications: Bus-Line

Digital inputs: 20Mounting: DIN rail

Description

The line-M-20l is a centraliser with 20 digital inputs that is designed to centralise the logical status of each signal or to count the number of impulses at each input.

Application

 \cdot Centralise consumption at installations such as: shopping centres, hotels, campsites, etc. \cdot Pulse receiver for water, gas and other meters.







Impulse centraliser

Code: M58E06.

Specifications

AC power supply			
Installation category	CAT III 300V		
auxiliary power supply mode	Through the connector		
DC power supply			
Consumption	3,5 W		
Nominal voltage	12 Vdc		
Mechanical characteristics			
Size (mm) width x height x depth	52.5 x 118 x 70 (mm)		
Screw type	Flat, M2.5		
Envelope	Self-extinguishing V0 plastic		
Torque setting	≤ 0,4 Nm		
Cable gauge at power supply terminals	2.5 mm ²		
Cable gauge at input and output terminals	2,5 mm ²		
Fastening	DIN rail (IEC 60715)		
Weight (kg)	0,3		
Environmental characteristics			
Protection class	IP30, Front: IP40		
Relative humidity (without condensation)	5 95%		
Storage temperature	-20 +70 °C		
Working temperature	-10 +50 ℃		
Voltage measurement circuit			
Input impedance	1.4 kΩ		
Standards			
Electrical safety, Maximum height (m)	2000		
Electrical safety, Installation category	CAT III 300 V		
Standards	UNE-EN 61010-1, UNE-EN 61000-6-2, UNE-EN 61000-6-4		
User interface			
	04150		
LED	21 LED		
LED Digital inputs	ZI LED		
	4,2 kVcc		







Impulse centraliser

Code: M58E06.

Consumption (per input)	60 mA Eingänge AUS / 240 mA Eingänge EIN
Туре	Optocoupler
Digital transistor outputs	
Maximum current	120mA

Line-M-20I

Expansion modules pulse inputs, Line series

CODE	TYPE	Protocol	N° relays	Digital inputs		
Input/Output Modules						
M58E06.	Line-M-20I	Modbus/RTU	-	20		

Transistor I/O expansion modules, Line system





Impulse centraliser

Code: M58E06.

Dimensions Connections







