

# Battery Tester With Color LCD Display MDXT-600

## User Manual



Thank you for purchasing our battery tester , please read this manual carefully and save it for reference before using !

**MDXT-600** battery tester is our newest version with color LCD Display. And it has a feature of review the latest 20 groups data. With the world's most advanced conductance testing technology, it can easily, quickly and accurately measure the actual cold cranking amps capability of the vehicle starting battery, healthy state of the battery, which can achieve quick vehicle repair.


### Product specification:

1. Application: 12V batteries and 12V&24V car system test
2. Measure Range:

Measure Standard	Measure Range
CCA	40-2000
BCI	40-2000
CA	40-2000
MCA	40-2000
JIS	26A17--245H52
DIN	40-1400
IEC	40-1400
EN	40-2000
SAE	40-2000
GB	3-220Ah

3. Working Environment Temp:-18°C-50°C
4. Special test clip: Double conductor Kelvin clamp
5. Housing Material: Acid-resistant ABS plastic
6. Measure Range: 3-220Ah
7. Voltage Measure Range: 7-30VDC

## Main functions:



According to the tester, you can press UP/DOWN key to choose:


- ① Out of Vehicle Test
- ② In Vehicle Test
- ③ Review
- ④ Language
- ⑤ Backlight
- ⑥ Version

## How to use:

### 1. CONNECTION

Connect the red test clamp with battery anode and the black one with cathode, the tester will power on automatically. Voltage battery below 7.0VDC can't be tested properly, then press ENTER key to continue.

### 2. OUT OF VEHICLE TEST



1).Select the battery type




2).Input rate capacity

TEST RESULT		
GOOD BATTERY		
HEALTHY	100%	785A
CHARGE	100%	12.66V
INTERNAL R	3.81mΩ	
RATED	550A	CCA

3).Battery test result

### Battery Test

### 3. IN VEHICLE TEST



**Notes:**1). If you only want to check battery healthy, choose Out of vehicle test function  
 2). Cranking and Charging System Test, choose In vehicle test function

### 4. REVIEW

Choose Review and press ENTER, you can see 20 groups of data

DATA 16		
GOOD BATTERY		
HEALTHY	91%	555A
CHARGE	98%	12.59V
INTERNAL R	5.37mΩ	
RATED	580A	CCA


### 5. LANGUAGE

English, French, German, Spanish, Italian, Portuguese, Russian

**Notes:**1). Other languages can be customized

### 6. BACKLIGHT

Choose IN THE ROOM or OUTSIDE, the backlight can be adjusted automatically.



## **After-sale warranty**

1. One Year warranty
2. The product passed CE, RoHS certification with quality and safety assurance
3. Add: 55# Gangda Avenue, North Section, Modern Industrial Port, Pixian, Chengdu, China
4. website: [www.lancol.com](http://www.lancol.com)