



Base unit, Harmony GTU, Premium **BOX for Universal Panel**

HMIG3UFC

Range of product	Harmony GTU
Product or component type	Base unit
Device short name	Premium Box
Range compatibility	Harmony GTU
[Us] rated supply voltage	1224 V DC power supply

Complementary

integrated connection type	Ethernet TCP/IP with 2 RJ45
	COM1 serial link RJ45 RS485 transmission rate: 110 1

115200 bit/s

COM1 serial link RJ45 RS485, transmission rate: 187.5 kbit/s
COM2 serial link SUB-D 9 RS232C/RS422/RS485, transmission rate: 110...115200 bit/s COM2 serial link SUB-D 9 RS232C/RS422/RS485, transmission rate: 187.5 kbit/s

Auxiliary port terminal block Expansion unit fieldbus card USB 2.0 port with 2 USB type A USB 2.0 port mini B USB

Modbus **Communication port protocol**

Uni-Telway

Modbus TCP/IP

Harmony Operating system

Software package Vijeo Designer run time

CPU RISC 600 MHz **Processor name**

Data storage equipment 1 GB SD card

10BASE-T/100BASE-TX/1000BASE-T **Port Ethernet**

Memory description 256 MB RAM internal

512 kB NVRAM backup memory

Type of cooling Natural convection

Width 188 mm

Height 131 mm

Depth 45 mm

Net weight 0.9 kg

Environment

Standards CSA C22.2 No 142

ANSI/ISA 12-12-01

UL 508

Class I division 2 CSA C22.2 No 213

IEC 61132-2

Product certifications	CE CULus ATEX IEC-Ex RCM GL KC CUL EAC ABS BV CCS DNV LR RINA UKCA UKEX
Ambient air temperature for operation	060 °C
Ambient air temperature for storage	-2060 °C
Pollution degree	2 conforming to EN 61131-2 Ed.3
Relative humidity	1090 % non-condensing
Operating altitude	2000 m
Vibration resistance	3.5 mm constant amplitude (f = 59 Hz) conforming to EN/IEC 61131-2 9.8 m/s ² (f = 9150 Hz) conforming to EN/IEC 61131-2
Electromagnetic compatibility	Electrostatic discharge immunity test level 3 conforming to EN/IEC 61000-4-2
Packing Units	
Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	13.5 cm
Package 1 Width	21.0 cm
Package 1 Length	26.0 cm
Package 1 Weight	1.091 kg
Unit Type of Package 2	S04
Number of Units in Package 2	4
Package 2 Height	30.0 cm
Package 2 Width	40.0 cm
Package 2 Length	60.0 cm
Package 2 Weight	4.944 kg
Offer Sustainability	
Sustainable offer status	Green Premium product
REACh Regulation	REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Mercury free	Yes
China RoHS Regulation	China RoHS declaration
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information


WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov


HMIG3UFC

Dimensions Drawings

Dimensions

External Dimensions





- 1 Front
- 2 Left
- 3 Bottom

Recommended replacement(s)