

Base unit, Harmony GTU, Premium BOX for Universal Panel

HMIG3U

Main

Range of product	Harmony GTU
Product or component type	Base unit
Device short name	Premium Box
Range compatibility	Harmony GTU
[Us] rated supply voltage	1224 V DC power supply

Complementary

Integrated connection type	Ethernet TCP/IP with 2 RJ45
----------------------------	-----------------------------

COM1 serial link RJ45 RS485, transmission rate: 110...115200 bit/s COM1 serial link RJ45 RS485, transmission rate: 187.5 kbit/s

COM2 serial link SUB-D 9 RS232C/RS422/RS485, transmission rate: 110...115200 bit/s

COM2 serial link SUB-D 9 RS232C/RS422/RS485, transmission rate: 187.5 kbit/s Auxiliary port terminal block

Expansion unit fieldbus card USB 2.0 port with 2 USB type A USB 2.0 port mini B USB

Communication port protocol Modbus

Modbus TCP/IP Uni-Telway

Operating system Harmony

Software package Vijeo Designer run time

Processor name CPU RISC 600 MHz

Data storage equipment 1 GB SD card

Port Ethernet 10BASE-TX/100BASE-TX/1000BASE-T

Memory description 256 MB RAM internal (2 x 13 mm board)

512 kB NVRAM backup memory

Type of cooling Natural convection

Width 188 mm

Height 131 mm

Depth 45 mm

Net weight 0.9 kg

Environment

Standards CSA C22.2 No 142

ANSI/ISA 12-12-01

UL 508

Class I division 2 CSA C22.2 No 213

IEC 61132-2

Product certifications	CE CULus ATEX IEC-Ex RCM GL KC CUL EAC ABS BV CCS DNV LR RINA UKCA UKEX
Ambient air temperature for operation	060 °C
Ambient air temperature for storage	-2060 °C
Pollution degree	2 conforming to EN 61131-2 Ed.3
Relative humidity	1090 % non-condensing
Operating altitude	2000 m
Vibration resistance	3.5 mm constant amplitude (f = 59 Hz) conforming to EN/IEC 61131-2 9.8 m/s² (f = 9150 Hz) conforming to EN/IEC 61131-2
Electromagnetic compatibility	Electrostatic discharge immunity test level 3 conforming to EN/IEC 61000-4-2
Packing Units	
Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	14.267 cm
Package 1 Width	21.441 cm
Package 1 Length	26.48 cm
Package 1 Weight	1.26 kg
Unit Type of Package 2	S04
Number of Units in Package 2	4
Package 2 Height	30 cm
Package 2 Width	40 cm
Package 2 Length	60 cm
Package 2 Weight	5762 g
Unit Type of Package 3	P12
Number of Units in Package 3	48
Package 3 Height	95 cm
Package 3 Width	80 cm
Package 3 Length	120 cm
Package 3 Weight	78144 g
Offer Sustainability	
Sustainable offer status	Green Premium product
REACh Regulation	REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration


Mercury free	Yes
China RoHS Regulation	China RoHS declaration
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
Contractual warranty	
Warranty	18 months


HMIG3U

Dimensions Drawings

Dimensions

External Dimensions





- 1 Front
- 2 Left
- 3 Bottom

Recommended replacement(s)