

Product data sheet

Specifications



iPRD8r modular surge arrester - 3P - IT - 460V - with remote transfert

A9L08321

Main

Range of product	Acti9
Product name	Acti9 iPRD
Product or component type	Surge arrester with pluggable cartridge
Device short name	iPRD8r
Device application	Distribution
Standards	EN 61643-11:2012 IEC 61643-11:2011
Product certifications	CE
Poles description	3P
Remote signalling	With
Signal contacts composition	1 SD (1 C/O)
Surge arrester type	Electrical distribution network
Earthing system	IT

Complementary

Surge arrester class type	Type 2 + 3
Surge arrester technology	MOV
[Ue] rated operational voltage	230/400 V AC (+/- 10 %) at 50/60 Hz
[In] nominal discharge current	Common mode: 2.5 kA (L/PE)
[Imax] maximum discharge current	Common mode: 8 kA L/PE
[Uc] maximum continuous operating voltage	Common mode: 460 V L/PE
Maximum [Up] voltage protection level	Common mode <1.6 kV type 2 L/PE Common mode <1.8 kV type 3 L/PE
[Ut] temporary overvoltage	337 V L/N 5 s withstand 1455 V L/PE 200 ms safe failure mode 1455 V N/PE 200 ms safe failure mode
[Isccr] short-circuit current rating	5 kA 415 V Ph/Ph
Disconnecter device type	Associated circuit breaker iC60L 10 A curve C - Icu 25 kA Associated fuse gG 25 A - Icu 15 kA Associated fuse gG 80 A - Icu 50 kA
Signalling circuit voltage	0.25 A/250 V AC 50/60 Hz

Mounting mode	Clip-on (DIN rail)
9 mm pitches	6
Height	85 mm
Width	54 mm
Depth	69 mm
Net weight	340 g
Colour	White (RAL 9003)
[Ipe] Ground residual current	0.6 mA
Connections - terminals	Tunnel type terminal (top or bottom) 2.5...25 mm² rigid Tunnel type terminal (top or bottom) 4...16 mm² flexible Tunnel type terminal (top or bottom) 4...16 mm² flexible with ferrule
Tightening torque	3.5 N.m

Environment

Relative humidity	5...95 %
Operating altitude	2000 m
Ambient air temperature for operation	-25...60 °C
Ambient air temperature for storage	-40...85 °C

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	6.3 cm
Package 1 Width	7.7 cm
Package 1 Length	9.3 cm
Package 1 Weight	380 g
Unit Type of Package 2	BB1
Number of Units in Package 2	4
Package 2 Height	10 cm
Package 2 Width	9 cm
Package 2 Length	28 cm
Package 2 Weight	1.602 kg
Unit Type of Package 3	S03
Number of Units in Package 3	36
Package 3 Height	30 cm
Package 3 Width	30 cm
Package 3 Length	40 cm
Package 3 Weight	14.953 kg

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant EU RoHS Declaration

Mercury free	Yes
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile

Recommended replacement(s)