

聚氨酯单管

PU Tube

产品特性/Product Features:

- 具有极好的柔软性、弯曲半径小、良好的抗震性、质轻、工作温度及工作压力范围宽。
- 具有极好的化学性能、压力损失小、硬度恒定、使用寿命长。
- 无毒、无味。
- 可按需定制颜色，易于管路识别。
- 符合ROHS环保要求。
- Excellent flexibility,small bending radius.good earthquake resistance, lightweight,wied range of temperature and working pressure.
- Excellent chemical properties, minimal pressure loss, constant hardness, long service life.
- Non-toxic,tasteless.
- Customer-made color is doable for easy pipeline recognition.
- Agree to ROHS environment protection requirement.



聚氨酯单管Y-PU/聚醚型单管Y-MPU

产品编码 Code		外径 O. D	内径 I. D	长度 Length	工作压力 Working Pressure	弯曲半径 Bending Radius
系列 Series	尺寸 Size	mm	mm	M	Kgf/cm ²	mm
Y-PU Y-MPU	0320	3	2	200	8	8
	0425	4	2.5	200	8	10
	0530	5	3	200	8	12
	0640	6	4	200	8	15
	0850	8	5	100	8	20
	1065	10	6.5	100	8	25
	1280	12	8	100	8	35
	1410	14	10	100	8	45
	1612	16	12	100	8	70

产品用途/Product Use:

- 工业机器人、气动工具、装配厂气压工具、带压输送管道。
- 过水及其他流体。
- 可用作真空吸管。
- 金属及电子产品的防护外套。
- 装饰品（如提手等）。
- Industrial robots, pneumatic tools, with pressure pipelines.
- Transport water and other fluid.
- Be used as a vacuum suction.
- Protection coat of the metal and electronic products
- Decorations(e.g.,handle,etc.).

温度范围:约-30℃到+80℃。
Temperature Range: approximately-30℃ to+80℃.
交货规格:可按需要定制外径从3mm至20mm的任意规格。
Specifications: O.D range from 3mm to 20mm.

工作压力曲线图Working Pressure Graph

