

MATERIAL SAFETY DATA SHEET

NIGLUBE RX-2

No. G2278

PRODUCT

SECTION I CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME : NIGLUBE RX-2
PRODUCT TYPE : Lubricating grease
MANUFACTURER'S NAME : Nippon Grease Co., Ltd.
ADDRESS : 4-11-28, Minami-Senba, Chuo-ku, OSAKA, 542-0081 Japan
TELEPHONE NUMBER : 06-6282-5411
EMERGENCY TELEPHONE NUMBER: 078-731-8147
DATE PREPARED : December 2, 2009

SECTION II COMPOSITION/INFORMATION ON INGREDIENTS

MIXTURE: Base oil, Thickener and Additives

INGREDIENTS AND COMPONENTS (% by mass):

Base oil (Polyalkylene glycol monoether)	Approx. 85
Thickener (Lithium soap)	Approx. 10
Additives (Anti-oxidant, anti-rust agent, etc.)	Below. 5

UN CLASS AND UN NUMBER:

SECTION III HAZARDS IDENTIFICATION

CLASS NAME OF HAZARDOUS CHEMICALS FOR SDS IN JAPAN: Not Applicable

SECTION IV FIRST-AID MEASURES

EYE CONTACT : Gently rinse the affected eyes with clean water for at least 15 minutes and consult an ophthalmologist.

SKIN : Wash the affected area under running water using a mild soap.

INHALATION : Remove the victim from the contamination immediately to fresh air.
Call a physician if symptom persists.

INGESTION : Do not induce vomiting. Call a physician.

SECTION V FIRE-FIGHTING MEASURES

EXTINGUISH MEDIA: Dry chemical, Foam, Carbon Dioxide

FIRE FIGHTING PROCEDURE : Fire-fighters should wear self-contained breathing apparatus with full-face piece operated in positive pressure mode.

SECTION VI ACCIDENTAL RELEASE MEASURES

Shut off all sources of ignition. Absorb spill with inert materials (e.g., dry sand or earth), then place in a chemical waste container with covers for disposal, using non-sparking tools.

SECTION VII HANDLING AND STORAGE

HANDLING: Avoid direct contact with skin or eyes.
Use in the well-ventilated areas.

STORAGE : Should be kept tightly sealed and stored in doors out of direct sunlight.
Keep away from sources of heat, open flames and sparks.
Avoid long storage periods since the product degrades with age.

SECTION VIII EXPOSURE CONTROL / PERSONAL PROTECTION

EXPOSURE:

ENGINEERING MEASURES: Do not use in areas without adequate ventilation.

EYE PROTECTION: Wear protective eyeglasses or chemical safety goggles if oil mist generated.

HAND,SKIN,AND
BODY PROTECTION : When prolonged or frequently repeated contact could occur, use protective clothing such as butyl rubber, impervious to this material.