



Ø 10
Clip für Direkt- und Leiterplattenmontage
Clip for Direct- and PCB-mounting

58 063 16



E186970


58 063 19




E186970

 mit Verdrehungsschutz
 with twist protection


58 063 17



63 017 01



63 017 01.3



Verpackungseinheit / Packing unit:	100 Stück / 100 pieces	100 Stück / 100 pieces	100 Stück / 100 pieces	1000 Stück / 1000 pieces	1000 Stück / 1000 pieces
IEC 60269-2	Kontaktclip Fuse-Clip PCB Mountable 58 063 16	Kontaktclip Fuse-Clip PCB Mountable 58 063 19	Kontaktclip Fuse-Clip PCB Mountable 58 063 17	Anschraubplatte Clamping Plate 63 017 01	Anschlusslasche Terminal Link 63 017 01.3
IEC 60269-3	10 x 38 mm				
IEC 60269-4	Bemessungsleistungsaufnahme 4 W / Rated Power Acceptance 4 W				
	Kupferlegierung CuSn, verzinnt / Copper alloy CuSn, tin-plated	Kupferlegierung CuSn, verzinnt / Copper alloy CuSn, tin-plated	Kupferlegierung CuSn, verzinnt / Copper alloy CuSn, tin-plated	Kupferlegierung CuSn, vernickelt / Copper alloy CuSn, nickel-plated	Kupferlegierung CuSn, versilbert / Copper alloy CuSn, silver-plated
A	11,0 mm	11,0 mm	11,0 mm	10,0 mm	21,0 mm
B	12,0 mm	12,0 mm	12,0 mm	9,0 mm	6,0 mm
C	18,0 mm	18,0 mm	18,0 mm	2,0 mm	2,0 mm
D	3,6 mm	3,6 mm	4,2 mm	4,2 mm	–
D1	–	–	–	–	M5
D2	–	–	–	–	M4
E	2,0 mm	–	–	–	15,5 mm
E1	–	2,0 mm	–	–	–
E2	–	3,0 mm	–	–	–
F	0,65 mm	0,65 mm	0,65 mm	–	11,0 mm
G	11,0 mm	11,0 mm	–	–	5,5 mm
H	4,45 mm	4,45 mm	–	–	–
I	1,5 mm	1,5 mm	1,5 mm	–	–
J	5,5 mm	5,5 mm	5,5 mm	–	–
K	–	–	–	–	–
L	11,5 mm	11,5 mm	11,5 mm	–	–
Gewicht/Weight kg/1	0,003	0,003	0,003	0,001	0,003